

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number  
**WO 2004/113005 A1**

- (51) International Patent Classification<sup>7</sup>: **B23D 79/02**, **B21C 37/08**
- (21) International Application Number:  
PCT/IT2004/000305
- (22) International Filing Date: 26 May 2004 (26.05.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
MO2003A000184 23 June 2003 (23.06.2003) IT
- (71) Applicant (for all designated States except US): **OTO MILLS, S.P.A.** [IT/IT]; Via Domenico Marchesi, 4, Zona Industriale Rondello, I-42022 Boretto (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **CHEZZI, Aleardo** [IT/IT]; Via Firenze 9, I-42022 Boretto (IT). **MICALI, Luciano** [IT/IT]; Viale Cappuccini, 14/2, I-42016 Guastalla (IT).
- (74) Agent: **GIANELLI, Alberto**; Bugnion S.p.A., No. 25 Via Emilia Est, I-41100 Modena (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A BEAD TRIMMER WITH A TOOL EXTRACTION SYSTEM



(57) Abstract: The bead trimmer is preferably applied in a production line for elements having longitudinal weld beads (21), where an element slides along a parallel direction to a longitudinal axis thereof (x), and comprises a tool-bearing turret (2) for removable fixing of a trimming tool (30), associated to a first slide (3) which is slidable along a horizontal direction (y) which is transversal with respect to the longitudinal axis (x) between an internal position, in which the tool (30) is aligned with the weld bead (21), and an external position, in which the tool (30) is not aligned with the weld bead (21), and (4) which is vertically slidable on a bearing structure (40) along a vertical direction (z) between a lowered position, in which the tool (30) is in contact with the weld bead (21), and a raised position, in which the tool (30) is distanced from the weld bead (21).